

## VISERA 4K UHD CAMERA CONTROL UNIT

# OTV-S400

The Core of Full 4K Image Reproduction.



# OTV-S400 – VIDEO SYSTEM CENTER

## 4K High-Quality Image Processing

- Wide color gamut
- 16-axial color-phase adjustment (more precise color setting based on surgeon's preference)
- Improved AE (automatic exposure) function

## Improved Operability

- Touch panel enables adjustments during procedure
- Easy registrations and loading of user presets

Innovation by  
**Sony & Olympus**



Specifications			
<b>Power Supply</b>	Rated voltage	220–240 V AC; within $\pm 10\%$	
	Rated frequency	50/60 Hz; within $\pm 1$ Hz	
	Rated input	350 VA	
<b>Size</b>	Dimensions (maximum)	390 (W) $\times$ 160 (H) $\times$ 506 (D) mm	
	Weight	13.5 kg	
<b>Observation</b>	Signal system	Corresponds to the 4K and HD	
	Signal output (resolution)	4096 $\times$ 2160, 3840 $\times$ 2160, or 1920 $\times$ 1080 can be selected	
	Signal output (transmission method)	3G-SDI or HD-SDI can be selected	
	White balance adjustment	Available	
	Standard color chart output	The "Color bar" screen can be displayed	
	Color tone adjustment	Red adjustment	$\pm 8$ steps
		Blue adjustment	$\pm 8$ steps
		Chroma adjustment	$\pm 8$ steps
	Automatic gain control (AGC)	The image can be electrically amplified when the light is inadequate due to the distal end of the endoscope being too far from the object	
	Contrast	Normal	Normal image
		High	Darkens the dark part and brightens the bright part compared to normal
		Low	Brightens the dark part and darkens the bright part compared to normal
	Iris Area	Auto	The exposure area is set automatically to obtain optimum brightness for the subject
		Center	Center-weighted measuring
Image enhancement settings	Fine patterns or edges in the endoscopic images can be enhanced electrically to increase the image sharpness		
	Either the structural enhancement or edge enhancement can be selected according to the user setup		
	Structural Enhancement	Enhancement of contrast of the fine patterns in the image	
NBI observation	Edge enhancement		
	Enhancement of edges of the endoscopic image		
NBI observation	This observation uses the narrow band observation light		
Endoscope's remote switches function	The functions of the remote switches on the endoscope can be set in the user presets		
<b>Documentation</b>	Displaying the record state	The recording state of the video recorder can be displayed on the monitor	
	Displaying the image information	The following data can be displayed on the monitor: · Zoom ratio / One-touch auto focus / Observation mode / NBI observation mode	
<b>Memory backup</b>	User presets	Up to 10 user presets can be registered	
	Memorization of selected settings	The following settings are held in memory even after the video system center is turned OFF: · System settings / Color tone / Color mode / Contrast / Enhancement / White balance	
<b>Classification (electro-medical equipment)</b>	Type of protection against electric shock	Class I	
	Degree of protection against electric shock of applied part	TYPE BF applied part	
	Degree of protection against explosion	The video system center should be kept away from flammable gases	

Specifications, design, and accessories are subject to change without any notice or obligation on the part of the manufacturer.

**OLYMPUS**

**OLYMPUS EUROPA SE & CO. KG**  
Postbox 10 49 08, 20034 Hamburg, Germany  
Wendenstrasse 14–18, 20097 Hamburg, Germany  
Phone: +49 40 23773-0, Fax: +49 40 233765  
www.olympus-europa.com

E0492368 · 1.000 · 10/15 · OEKG · ED